

Features and Benefits

- » An RG6 metre marked cable with quadshielding white in colour
- » Sold in a 305 metre reel
- » Suitable and approved for Pay and Digital TV
- » Foxtel Approved (F30866), Optus (SAP4868)
- » Suitable for White Fly Leads to blend in




Coaxial Cable

Matchmaster has a complete range of PAY TV and FTA approved cables for both commercial and residential applications. Matchmaster's range includes standard, flooded, messengered, Tri-Shield and Quad Shield RG6 and RG11 cable. Also available White approved RG6 Quad Shield cable for indoor use. Whatever the application Matchmaster has the cable to suit.



Technical Data 06MM-E6QWH

Construction		
Inner Conductor	Material	Copper Clad Steel Wire
	Diameter (mm)	1.02±0.01
Insulation	Material	Physically Foamed PE
	Diameter, mm	4.57±0.15
Outer Conductor	1st shield	Bonded Al/PET/Al Tape 4.78 ±0.13
	2nd shield	Al-Mg Alloy Wire Braid
	3rd shield	Non-bonded Al/PET/Al Tape
	4th shield	Al-Mg Alloy Wire Braid
Jacket	Material	FR PVC or PVC
	Diameter, mm	7.54±0.20
Mechanical Properties		
Bending	Single	35
Radius, mm	Typical	70
Pulling Strength, N		200
Adhesion Force, N		>20
Electrical Properties		
Impedance, Ω		75±3
DCR of Inner conductor, Ω /km		102.0
DCR of outer conductor, Ω /km		19.1
Capacitance, pF/m		54
Propagation Velocity, %		82
DC Breakdown Voltage, kV		5.0
Insulation Resistance, MΩ·km		>1x10 ⁴
Screening Attenuation, dB	>105@5-1000MHz	
	>95@1000-2000MHz	
	>85@2000-3000MHz	



Attenuation	
Frequency MHz	Max. attenuation @20°C,dB/100m
5MHz	1.90
55MHz	5.25
211MHz	10.00
250MHz	10.82
270MHz	11.04
300MHz	11.64
330MHz	12.26
350MHz	12.63
400MHz	13.61
450MHz	14.43
500MHz	15.29
550MHz	16.08
600MHz	16.73
750MHz	18.54
870MHz	20.04
1000MHz	21.49
1300MHz	24.49
1450MHz	25.89
1750MHz	28.67
2150MHz	31.79
2600MHz	35.30
2832MHz	37.74
3000MHz	38.84
Return Loss, dB	
5-3000MHz	≥20
Standards	
2011/65/EU	Compliant