

5 Wire Multiswitch 5 In 8 Out Remote Powered 21MM-MV508



Features and Benefits

- » Foxtel approved (F30822)
- » Suitable for large installations of SAT IF distribution systems
- » Length of the subscriber line up to 80 meters (must meet Pay TV provider specifications)
- » Four positions discrete gain regulator for each SAT IF line and separate 16 positions discrete gain regulator for terrestrial TV
- » Active terrestrial TV path powering from central power supply allows to receive terrestrial TV programs without switching on SAT TV receiver
- » Used with 5 Wire products only



Line Powered Specifications

Foxtel Approval Number		F30287
Frequency Range	SAT IF	950-2400 MHz
	Terr. TV	47-862 MHz
SAT IF Gain (fixed slope pre-correction)	Outputs 1-4	5 \div 14dB
	Outputs 5-8	4 \div 12dB
Terr. TV Gain (fixed slope pre-correction)	Outputs 1-4	-1 \div 5dB
	Outputs 5-8	-2 \div 3dB
Gain Adjustment SAT IF		12dB by 4dB Step
Gain Adjustment Terr. TV		15dB by 1dB Step
Output Level for SAT IF (IMD3=35dB)*		105dB μ V

Output Level for Terr. TV (IMD3=60dB)*	Outputs 1-4	88dB μ V
	Outputs 5-8	86dB μ V
SAT Inputs Decoupling		\geq 30dB
Outputs Decoupling	SAT IF	\geq 30dB
	Terr. TV	\geq 35dB
Rejection	Terr. TV/SAT	\geq 30dB
	SAT/Terr. TV	\geq 40dB
Consumption From Receiver		<65mA
Consumption From Inputs H Lines or External Power Supply		+18 V 60mA
Control Signals		14/18V, 0/22kHz
Dimensions		187 x 135 x 30mm
Weight		0.6kg

* 2 Equal Carriers