

2 Way HDMI 2.0 Splitter with Built-In Downscaler 34MM-HDS2



For the Best

HDMI 2.0 Scaler Splitter 2 way with Scaler built in to allow 4K signal to be downscaled to 1080p to allow content to be shared across 2 displays with different resolution capability.

Features and Benefits

- » HDMI 2.0b, HDCP 2.2 compliant
- » Supports resolutions up to 4K2K@60Hz with 24bit RGB/YCBCR 4:4:4
- » EDID control with 8 settings and HDCP switch
- » Supports LPCM 7.1CH, Dolby TrueHD, and DTS-HD Master Audio
- » Threaded DC power port for secure power supply connection
- » Compact design for an easy and flexible installation

18Gbps

4K HDR

Ultra HD

COMPATIBLE



34MM-HDS2 Specifications

| Video Input | |
|------------------------|-----------------------------|
| Input | (1) HDMI |
| Input Connector | (1) Type-A female HDMI |
| HDMI Input Resolution | Up to 4Kx2K@60Hz 4:4:4 8bit |
| HDMI Standard | 2.0 |
| HDCP Version | 2.3, 1.4 compliant |
| CEC | Supported |
| Video Output | |
| Output | (2) HDMI |
| Output Connector | (2) Type-A female HDMI |
| HDMI Output Resolution | Up to 4Kx2K@60Hz 4:4:4 8bit |
| HDMI Standard | 2.0 |
| HDCP Version | 2.3, 1.4 compliant |
| CEC | Supported |
| Control | |

| Control Part | (1) EDID 4-pin DIP switch, (1) Micro-USB port |
|-----------------------|---|
| General | |
| Bandwidth | 18Gbps |
| HDMI 2.0 Cable Length | 4K@60Hz 4:4:4 ≤ 5m, 4K@60Hz 4:2:0 ≤ 15m, 1080p ≤ 20m |
| Operation Temperature | -10°C ~ +55°C |
| Storage Temperature | -25°C ~ +70°C |
| Relative Humidity | 10%-90% |
| Power Supply | Input:100V~240V AC; Output: 5V DC 1A |
| Power Consumption | 1.5W (Max) |
| Dimension (WxHxD) | 96.0 x 17.6 x 70.4mm |
| Net Weight | 185g |

Note: Please adopt high-qualified HDMI cable fully compliant with HDMI 2.0 for reliable transmission and connection.