

5MP HD Bullet IP PoE Camera

IP66 3.6MM Fixed Lens

50MM-CB001

50MM-CB001 is a 5MP IP PoE Bullet camera suited for use both indoor and outdoors. The CB001 is IP66 waterproof rated and features an IR range up to 20m. Featuring a 3.6mm fixed lens with a 1/2.8" Sony IMX335 Low light CMOS sensor, Digital Wide Dynamic Range and Ultra low illumination at 0.01Lux.

Features and Benefits

- » ONVIF 17.06 compatible for simple communication and mobile viewing
- » 5MP resolution 2592 x 1944 at 15 frames per second or 4MP at 25 frames per second
- » Fixed 3.6mm lens with a 1/2.8" Sony IMX335 Low light CMOS sensor
- » 12pcs SMD IR Led with IR distance of 20m
- » Supports RTSP/FTP/DHCP/DDNS/NTP/SMTP/NFS protocols
- » Supports H.265/H.264 video standards



50MM-CB001 Specifications

Camera	
Image Sensor	1/2.8" Sony IMX335 CMOS
Effective Pixels	2592x1944 (HxV)
Electronic Shutter	AUTO, 1/25s - 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Indoor/Outdoor
AGC/BLC	Support
DNR	2D/3D DNR
Other	Motion Detection, Privacy Mask, Mirror, flip
Encode	
Embedded Solution	Mstar 316DM
Video Standard	H.265/H.264
Video Resolution	Main Stream:15fps@ 5MP(2592*1944), 25fps@ 4MP(2592*1520) Sub Stream: VGA(640x480)/ 360P@25fps, etc.
Video Bitrates	32Kbps - 6Mbps, VBR/CBR

Lens	
Focal length	3.6mm lens
Optional Function	
POE, Audio, Alarm In/Out, SD card, etc.	
Network Services	
Protocol	RTSP/FTP/DHCP/NTP etc.
P2P	Yes
Web	IE, Firefox, etc.
Media	CMS, Android, iOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC 3 10%
Power Consumption	<10 W
Operating Temp.	-30°C-(+60)°C, 10%-90%RH