

2MP HD Dome IP Wi-Fi Camera IP66


3.6mm Fixed Lens

50MM-CWD01

CWB01 is a 2MP IP Wi-Fi Bullet camera suited for use both indoor and outdoors. The CWB01 is IP66 waterproof rated and features an IR range up to 25m. Featuring a 3.6mm fixed lens with a 1/2.7" Progressive Scan Sensor. Featuring Digital Wide Dynamic Range and Ultra low illumination.

Features and Benefits

- » Fixed 3.6mm lens with a 1/2.7" Full HD CMOS Progressive Scan Sensor
- » 1920*1080@1-15fps (default resolution:1920*1080/frame rate:15fps/bit rate:1Mbps)
- » Cameras weather-resistant rated to IP66 for indoor and outdoor use
- » IR night vision to capture video up to 20M to protect your property 24 hours a day
- » Saturation/Brightness/Contrast /Sharpness, Mirror, White Balance, FLK(Flicker Control)
- » Can be added to any 50MM-NWxx-x Matchmaster series Wi-Fi NVR's



2MP HD Dome IP Wi-Fi Camera IP66
3.6mm Fixed Lens
50MM-CWD01



For the Best

50MM-CWD01 Specifications

Camera	
Image Sensor	1/2.7" Full HD CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1920 x 1080 (HxV)
Compression	H2.264/H2.64+/H2.65/H2.65+
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Wireless network
Reset Button	Yes
Lens Type	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	3MP
Night Vision	
Infrared LED	14μ x 12PCS
Infrared Distance	20M
IR Status	Auto Control
IR Power On	Auto Control
Network	
Protocol	TCP/IP, ICMP, RTP, RTSP, RTCP
Main Stream 1	1920 x 1080@1-15fps (default resolution:1920 x 1080/ frame rate 15fps/ bit rate1Mbps)
Sub Stream 1	720 x 480@1-15fps(default frame rate 15fps/bit rate0.5Mbps)
Wireless	
Antenna	3dBi
Hotspot	No
Wi-Fi	Wi-Fi (IEEE802.11b/g/n)
Wi-Fi Range	No obstacles 300m Max
Camera Feature	
Day/Night	Colour/B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, White Balance, FLK (Flicker Control)
Defog Mode	Yes
BLC	Yes
WDR	Yes
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR
Interface	
Audio	Built in audio
General	
Housing	Metal, IP66
Anti-cut Bracket	Optional Wall Bracket
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH 95% Max
Storage Temperature	-20°C ~ + 60°C RH95% Max
Power Source	DC12V±10%, <500mA
Dimension	94 x 94 x 72mm (WxHxD)
Weight	400g