

4/5MP HD Bullet IP Camera LAN POE IP66 3.6mm Lens 2592x1520 Res 50MM-LB5MPFLIR20



For the Best

Features and Benefits

- » ONVIF industry standard support mobile viewing
- » 4 mega pixel HD resolution 2592x1520
25/30 FPS 15FPS @ 5MP
- » POE LAN connection
- » Ingress protection rating IP66
- » IR distance 15-20m
- » 3.6mm lens

Security

Matchmaster security systems are suitable for home, offices including small business applications. These systems use the latest technology in IP and network video recording offering full HD 1080P all the way to 4K high resolution. These systems come in wired and wireless configurations with high grade video processing and recording capacity up to 24TB (6TBx 4HDD)



50MM-LB5MPFLIR20 Specifications

Camera	
Image Sensor	1/3" OV4689 CMOS
Effective Pixels	2688 (H) x 1520 (V)
Electronic Shutter	AUTO, 1/25s - 1/100000s
Min. Illumination	0.1Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
AGC/BLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
Encode	
Embedded Solution	Hi3516D
Video Standard	H.265/H.264
Video Resolution	Main Stream: 15fps@5MP (2592x1944), 25fps@4MP (2592x1520), 30fps@3MP/1080P /720P Sub Stream: VGA(640x480)/360P/QVGA@25fps, etc.
Video Bitrates	32Kbps - 8Mbps, VBR/CBR
OSD Overlay	Title and Time overlay
IR Led	
IR Led	8 pcs small array IR Leds
IR Distance	15-20 M



Lens	
Focal length	HD 3.6 mm fixed lens
Network Services	
Protocol	HTTP/RTSP/FTP/NFS/SMB/DHCP/NTP, etc.
P2P	Yes
Web	IE, Firefox, etc.
Media	CMS, Android, IOS
ONVIF	2.4 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC ± 10%
Power Consumption	< 8 W
Operating Temp	-30°C-(+60)°C, 10%-90%RH