

5MP Pan/Tilt/Zoom IP LAN (POE) Full High Definition Bullet Camera 50MM-LB5MPVLIR40

Features and Benefits

- » UHD resolution 2592x1944P
- » High sensitivity, ultra low 0.05Lux; 0.00Lux IR on, 40m IR range
- » 1/2.9" Sony IMX326 CMOS sensor, HD 2.7-13.5 mm AF lens
- » Support user authentication, video data encryption
- » Lightning protection 4000V, IP65 strong water-proof housing
- » Network PTZ control, Pan: 0° ~ 180°; Tilt: 0° ~ 60°

50MM-LB5MPVLIR40 Specifications

| | |
|--------------------|--|
| Camera | |
| Image Sensor | 1/2.9" 6.82MP IMX326 CMOS |
| Effective Pixels | 2688(H)x1520 (V) |
| Electronic Shutter | AUTO, 1/25s ~ 1/100000s |
| Min. Illumination | 0.05Lux@F1.2(AGC ON), 0Lux IR on |
| Day/Night | Auto/Color/(B/W)/Timing |
| WDR | Digital WDR |
| White Balance | Auto |
| AGC/BLC | Support |
| DNR | 2D/3D DNR |
| Other | Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate |
| Encode | |
| Embedded Solution | Hi3516D |
| Video Standard | H.265/H.264 |
| Video Resolution | Main Stream: 18fps@5MP(2592x1944), 25fps@4MP(2592x1520), 30fps@3MP/1080P/720P Sub Stream: VGA(640x480)/360P/ QVGA@25fps, etc. |
| Video Bitrates | 32Kbps - 8Mbps, VBR/CBR |
| Audio Standard | G.711-u/G.711-a |
| OSD Overlay | Title and Time overlay |
| IR Led | |
| IR Led | 6 pcs SMD array IR Led |
| IR Distance | 30-40M |
| Lens | |
| Focal length | 2.7-13.5 mm AF lens |
| Zoom | 5x optical zoom |

Security

Matchmaster security systems are suitable for home, offices including small business applications. These systems use the latest technology in IP and network video recording offering full HD 1080P all the way to 4K high resolution. These systems come in wired and wireless configurations with high grade video processing and recording capacity up to 24TB (6TBx 4HDD)



| | |
|----------------------|---------------------------------------|
| PTZ | |
| Pan/Tilt Range | Pan: 0° ~ 180°; Tilt: 0° ~ 55° |
| Preset Point | 1 |
| Manual Control Speed | Pan: 0.5° ~20° /s; Tilt: 0.5° ~10° /s |
| Guard Position | Support |
| Power-off Recovery | Support |
| Network Services | |
| Protocol | HTTP/RTSP/FTP/NFS/SNMP/DHCP/NTP, etc. |
| P2P | Yes |
| Web | IE , Firefox, etc. |
| Media | CMS, Android, iOS |
| ONVIF | 2.6 compatible |
| General | |
| Network Port | 1-RJ45, 100Mbps, POE optional |
| Power Supply | 12 VDC 3 10% |
| Power Consumption | < 10 W |
| Operating Temp. | -20°C-(+60)°C, 10%-90%RH |