

4/5MP HD Dome IP Camera LAN POE IP66 3.6mm Lens 2592x1944 Resolution 50MM-LD5MPFLIR35

Features and Benefits

- » ONVIF industry standard support mobile viewing
- » 4 mega pixel HD resolution 2592x1944
20/30 FPS 15FPS @ 5MP
- » POE LAN connection
- » Ingress protection rating IP66
- » IR distance 20-35M
- » 3.6mm lens

50MM-LD5MPFLIR35 Specifications

Camera	
Image Sensor	1/3" OV4689 CMOS
Effective Pixels	2688x1520 (HxV)
Electronic Shutter	AUTO, 1/25s - 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
AGC/BLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
Encode	
Embedded Solution	Hi3516D
Video Standard	H.265/H.264
Video Resolution	Main Stream: 15fps@5MP(2592x1944), 25fps@4MP(2592x1520), 30fps@3MP/1080P/720P Sub Stream: VGA(640x480)/360P/ QVGA@25fps, etc.
Video Bitrates	32Kbps - 8Mbps, VBR/CBR
Audio Standard	G.711-u
IR Led	
IR Led	6pcs Array IR Leds
IR Distance	20-30M
Lens	
Focal Length	3.6mm Fixed Lens



Optional Function	
POE, Audio, SD card, etc.	
Network Services	
Protocol	HTTP, RTSP, FTP, NFS, SMTP, DHCP, NTP, etc.
P2P	Yes
Web	IE, Firefox, etc.
Media	CMS, Android, iOS
ONVIF	2.4 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC 3 10%
Power Consumption	<8W
Operating Temp.	-20°C-(+60)°C, 10%-90%RH